

Stellar Kiosk

POSIFLEX™



Countertop model

Pedestal model

KEY FEATURES

- Vibrant, high definition 21.5" PCAP touch screen
- Intel® Celeron® J1900, 2MB Cache, 2.0GHz or Intel® Core™ i3-7100U, 3MB Cache, 2.40GHz or Intel® Core™ i5-7200U, 3MB Cache, 2.50GHz
- Sleek, durable enclosure
- Modular design
- Pedestal or countertop models
- Internal speakers
- Comes conveniently shipped in manageable boxes—no bulky wooden crate. Some assembly may be required.
- Includes monitor, CPU, 3" thermal printer, customer-facing camera, WiFi, proximity sensor, service indicator, pedestal base and base plate

Options*:

- 2D barcode scanner
- NFC
- MSR
- MSR with fingerprint sensor
- Customized bracket for EMV payment devices

* Some options may require assembly or installation at customer site. On-site installation services available for an additional charge.

Combining Stellar Design and Performance

The Stellar TK2100 enclosure features an All-in-One PC and projected capacitive touchscreen with a minimalist bezel, providing a contemporary and sophisticated user interface presentation. The Stellar Series is available as a free-standing pedestal or a countertop model, providing modular

deployment options for both models. The enclosure comes with preferred components common to most self-service transactions, including a barcode scanner and receipt printer, and can be customized with EMV payment devices and more. The entire kiosk is modular for ease of transporting

and modules are efficiently boxed and palletized for more compact and cost-efficient shipping. The Stellar is configured for easy maintenance with hinged doors and simple component access. ADA compliant design ensures self-service access to all your valued customers.




Modular for ease of transporting and significantly lower shipping costs

Stellar Kiosk

Specifications		TK2130	TK2150
Processor	Intel® Celeron® J1900, 2MB Cache, 2.0GHz		Intel® Core™ i3-7100U, 3MB Cache, 2.40GHz Intel® Core™ i5-7200U, 3MB Cache, 2.50GHz
System Memory	1x slot 4GB DDR3L SO-DIMM (Max. 8GB), 1333MHz, 1.35V		2x slots 4GB DDR4 SO-DIMM 1200MHz 1.2V (Max. 32GB)
Storage device	128GB SATA		
Supported OS	Windows POSReady 7/Windows 10 IoT Enterprise		
LAN Port	1x Gigabit LAN		
Audio	Integrated Dual Amplified Speakers		
Internal Expansion Slot	1 x M.2		
Built-in Printer	3" detachable printer w/ auto cutter, 200 mm/sec (max.)		
Display & Touch			
LCD	21.5"		
Resolution	1920 x 1080		
Touch	True-Flat Projected Capacitive with Multi-touch support		
Physical Dimensions			
Dimensions (W x D x H in inches)	Main unit: 15.7 x 18.1 x 32.9 With pedestal: 24.6 x 24.0 x 63.8		
Weight (N. W. in lbs)	Main unit: 60.6; With pedestal: 132.3		
Environment			
Operating Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)		
Storage Condition	-20°C - 70°C, 10%RH - 90%RH		
Built-in Options * for Pedestal			
WiFi/Bluetooth	802.11ac, Dual Band 2.4GHz / 5GHz; BT 4.2, M.2 module		
Scanner	2D barcode scanner		
Proximity Sensor	Range from 45 cm to 80 cm		
Camera	1MP wide angle camera		
EMV Payment Device Bracket Support	Custom bracket support for various EMV payment devices		
MSR	3 tracks ISO or JISII (HID/VCOM selection)		
Fingerprint Sensor	Optical type		
RFID Reader	Support ISO/IEC 14443-A&B (MIFARE), JIS x 6319-4 (Felica), ISO/IEC 15693, NFC protocols - tag read/write (ISO/IEC-18902)		
Status Indicator	3-color LED indicator		

* Some options may require assembly or installation at customer site. On-site installation services available for an additional charge.

** The product information and specifications are subject to change without prior notice.



Standard package comes shipped with display unit + pedestal base + base plate. Shipped in two boxes.

Required assembly: Attach base plate to bottom of pedestal base, and attach top of pedestal base to bottom of display unit with included screws.



POSIFLEX™

Posiflex Business Machines, Inc.
30689 Huntwood Ave.
Hayward, CA 94544
P: 888-968-1668
F: 510-475-0982
sales.department@posiflexusa.com
www.posiflexusa.com