

RT6000 Series

POSIFLEX™



KEY FEATURES

- 15"/4:3 standard or 15.6"/16:9 widescreen with projected capacitive touch screen
- Slim, yet Powerful
 - Intel® Core™ i3-8145UE or i5-8365UE processor
 - Diverse I/O ports
- Patented Fanless Technology
 - Easy to clean and very durable
 - Spill and dust resistance
 - Fanless unit runs silently and provides a long service life
- Clean Cable Management
 - Advanced cable management design provides easy system upgrade and maintenance
- Faster Installation and Serviceability
 - Rear cover can be easily removed, allowing for quick access
- Save Time and Money
 - Can be shipped with customer line display or 10"/4:3 or 11"/16:9 secondary customer-facing LCD display attached and folded, resulting in reduction of the package size and weight, saving deployment time and shipping costs

Power. Performance. Elegance.

The RT6000 Series radiates an ultra-slim design and a sleek look that exhibits sheer elegance. Because of its slim profile, it takes up less counter space and provides better cable management and easy maintenance. The RT6000 is taking POS terminal design into the next level, setting your brand image apart from the others.

With its sleek contours, ultra-slim body, and linear rear cover surface, the RT6000 Series features a 15" [standard] or 15.6" [widescreen] projected capacitive touch screen, and a full suite of ports that are neatly hidden under the rear cover. No screws can be found on its surface maintaining its clean and sleek look.

Advanced cable management design delivers a truly clutter-free station. The standard base can house the optional Powered USB or USB extension module, while the optional base integrates a UPS backup (RB5000) for the event of a power failure.

RT6000 Series

Specifications	RT6015	RT6016
Processor	Intel® Core™ i3-8145UE, 4MB Cache, 2.20GHz Intel® Core™ i5-8365UE, 6MB Cache, 1.60GHz	
System Memory	2x slots 4GB DDR4 SO-DIMM 2400MHz 1.2V (Max. 32GB)	
TPM Support	TPM 2.0	
Storage Device	128GB SSD or higher. Up to two drives.	
Supported OS	Windows 10 IoT Enterprise 64bit	
Touch	True-Flat Projected Capacitive with Multi-touch support	
Physical Dimensions		
Dimensions (WxDxH) in.	14.5 x 8.14 x 12.8	15.8 x 8.14 x 11.6
Display	15"; 4:3 ratio; 1024x768	15.6"; 16:9 ratio; 1920x1080
Weight (lbs)	12	11
VESA Mount	75mm	
Connectivity		
LAN Port	1 x Gigabit LAN	
Serial Port	1 x DB9 Serial; 2x RJ-50 Serial (5v/ 12v support on all COM ports)	
Display Port	1 x Mini DP; 1 x Proprietary internal VGA port for Posiflex Secondary Monitors	
USB Port	2 x USB 3.0; 3 x USB 2.0	
Audio	1 x Internal 2W speaker	
CR PORT	1 x RJ-11 (Controls 2 drawers Dual Independent Sensor 24v)	
Options		
Powered USB	Powered USB module with 24v +12v (1x USB 3.0 port will no longer be available with the Powered USB module)	
USB Hub	USB hub module to allow for 7 USB ports on system	
WiFi/Bluetooth	802.11ac, Dual Band 2.4GHz / 5GHz; BT 4.2, M.2 module	

** The product information and specifications are subject to change without prior notice.



Posiflex designs, engineers and manufactures:

Touch Screen Terminals | Tablets | Kiosks | Printers | Magnetic Stripe Readers | Cash Drawers | Rear/Pole Displays

Rev. 113022

POSIFLEX™

Posiflex Business Machines, Inc.
30689 Huntwood Ave.
Hayward, CA 94544

P: 888-968-1668

F: 510-475-0982

sales.department@posiflexusa.com

www.posiflexusa.com