

RT1016

POSIFLEX™



KEY FEATURES

- 15.6"/16:9 widescreen display with projected capacitive touch screen
- Powered by a Rockchip RK3399 processor for Android 9.0, with 4GB DDR4 memory and 32 GB eMMC
- Slim, Stylish Look
 - Sleek contours, ultra-slim body
 - Full suite of ports neatly hidden under rear cover
- Patented Fanless Technology
 - Easy to clean and very durable
 - Spill and dust resistance
 - Fanless unit runs silently and provides a long service life
- Clean Cable Management
 - Advanced cable management design provides easy system upgrade and maintenance
- Faster Installation and Serviceability
 - Rear cover can be easily removed, allowing for quick access
- Save Time and Money
 - Can be shipped with secondary customer-facing LCD display attached and folded, resulting in reduction of package size and weight, saving deployment time and shipping costs

Stylish, Versatile Workhorse

Part of the excellent, sleek line of Posiflex's RT Series, the RT1016 is the Android OS version, equipped with Android 9.0, 4GB DDR4 and 32GB eMMC. The RT1016 terminals not only delivers

powerful performance but features an ultra-slim look that exhibits elegance. It is also impressively compact, provides excellent cable management and is easy to maintain, boasting a convenient removable

and screwless back panel. The RT1016 is taking POS terminal design into the next level, setting your brand image apart from the others.



RT1016

Specifications

Processor	Rockchip RK3399, Cortex® A72 + A53 (up to 2.0GHz), Integrated Mali T860 GPU
System Memory	4GB DDR4
Storage Device	32 GB eMMC + microSD slot x 1
Supported OS	Android 9.0; Android 10 with GMS
Touch	True-Flat Projected Capacitive with Multi-touch support

Physical Dimensions

Dimensions (WxDxH) in.	15.8 x 8.15 x 11.7
Display	15.6"; 16:9 ratio; 1920x1080
Weight (lbs)	11.0

Connectivity

LAN Port	1 x Gigabit LAN Port
Serial Port	1 x DB9 Serial; 1 x RJ-50 Serial (5v/12v support on all COM ports)
Display Port	1 x HDMI; 1 x Proprietary internal VGA port for Posiflex Secondary Monitors
USB Port	1 x USB 3.0; 4 x USB 2.0
Audio	1 x Internal 2W speaker
CR PORT	1 x RJ-11 (Controls 2 drawers. Supports 24v power only)

Options

Mini-PCIe WiFi/BT module	802.11ac, Dual Band 2.4GHz / 5GHz
--------------------------	-----------------------------------

Optional Attachments

PD-2610UE-B	2x20 VFD rear mounted customer display, USB interface (USB/VCOM selectable) for RT series, black
RA-301	3-in-1 Attachment for 15" RT series with 3 track MSR, optional fingerprint sensor + 2D scanner
LM-4011	Secondary 10.1" LCD Display (16:9 Ratio 1280 x 720 resolution) for 15.6" RT Series
TM-4011	Secondary 10.1" LCD Touch Monitor (16:9 Ratio 1280 x 720 resolution) for 15.6" RT Series
RA-101	3 Track Encryption Capable MSR for 15" or 15.6" RT Series
RA-104	2D Barcode Imager attachment for 15" or 15.6" RT series
RA-301	3 Track Encryption Capable MSR, with optional Fingerprint Sensor and 2D Barcode for 15" or 15.6" RT series
WB-4200	Wall Mount Bracket for RT Series

** The product information and specifications are subject to change without prior notice.



Posiflex designs, engineers and manufactures:

Touch Screen Terminals | Tablets | Kiosks | Printers | Magnetic Stripe Readers | Cash Drawers | Rear/Pole Displays

Rev. 113022

POSIFLEX™

Posiflex Business Machines, Inc.
30689 Huntwood Ave.

Hayward, CA 94544

P: 888-968-1668

F: 510-475-0982

sales.department@posiflexusa.com

www.posiflexusa.com